

Slimline LED Avant



Difusor
Diffuser
Diffuseur
Difusor




Color
Colour
Couleur
Cor



Cuerpo
Body
Corp
Corpo

CÓDIGO	POTENCIA	FLUJO	CCT	DIMENSIONES (x-y-z)
548564	4W	364lm	3000K	325 x 24 x 38mm
548571	4W	372lm	4000K	325 x 24 x 38mm
548588	4W	385lm	6500K	325 x 24 x 38mm
548595	10W	891lm	3000K	585 x 24 x 38mm
548601	10W	927lm	4000K	585 x 24 x 38mm
548618	10W	963lm	6500K	585 x 24 x 38mm
548625	14W	1271lm	3000K	885 x 24 x 38mm
548632	14W	1302lm	4000K	885 x 24 x 38mm
548649	14W	1353lm	6500K	885 x 24 x 38mm
548656	18W	1602lm	3000K	1.185 x 24 x 38mm
548663	18W	1656lm	4000K	1.185 x 24 x 38mm
548670	18W	1728lm	6500K	1.185 x 24 x 38mm
548687	23W	2047lm	3000K	1.498 x 24 x 38mm
548694	23W	2116lm	4000K	1.498 x 24 x 38mm
548700	23W	2208lm	6500K	1.498 x 24 x 38mm



INFORMACIÓN

INFORMATION

INFORMATION

INFORMAÇÕES

- N** • Máximo empalmable 20m lineales.
- Empalme de 15cm incluido.
- Cable de alimentación de 1m.
- E** • 20m-in-line maximum for joint.
- 15cm junction included.
- Power cable 1m.
- I** • Maximale 20m en ligne pour joint.
- 15cm jonction inclus.
- Câble d'alimentation 1m.
- P** • União máxima em linha de 20m
- 15cm da junção incluído.
- Cabo de alimentação 1m.



TENSIÓN: 220~ 240V
CLASE: II
ÁNGULO DE APERTURA: 160°
LÁMPARA: Módulo LED lineal
HORAS DE VIDA: 30.000h
COLOR: Blanco
CUERPO: Aluminio
DIFUSOR: Policarbonato opal

VOLTAGE: 220~ 240V
CLASS: II
ANGLE: 160°
LAMP: Linear LED module
LIFETIME: 30.000h
COLOR: White
BODY: Aluminium
DIFFUSER: Opal polycarbonate

TENSION: 220~ 240V
CLASSE ÉLECTRIQUE: II
ANGLE D'OUVERTURE: 160°
LAMPE: Module LED linéaire
HEURES DE VIE: 30.000h
COULEUR: Blanc
CORPS: Aluminium
DIFFUSEUR: Polycarbonate opale

TENSÃO: 220~ 240V
CLASSE: II
ÂNGULO DE ABERTURA: 160°
LÂMPADA: Módulo LED linear
VIDA: 30.000h
COR: Branco
CORPO: Alumínio
LENTE: Policarbonato opal