



**5** Hasta cinco años de garantía  
Up to five years of warranty  
Jusqu'à cinq ans de garantie  
Até cinco anos de garantia


Leyenda  
Map key  
Légende  
Legenda




- A+
- CII
- IP20
- 45°
- >80 lm/w icon"/> >80
- 50.000h
- >50.000h
- 25°
- AL
- Ø75-80mm

**N**/ NAVI REGULABLE de serie: Apto para regulador convencional de incandescencia/TRIAC. Cabezal basculante. **E**/ DIMMABLE NAVI serial: Suitable for conventional incandescent regulator/TRIAC. Tilt head. **F**/ NAVI DIMMABLE en série: Suitable for conventional incandescent regulator/TRIAC. Tête pivotante. **P**/ NAVI REGULÁVEL de Série: Apropriado para regulador incandescente convencional/TRIAC. Orientável.

	W	⚡	φ	K	⊗	⊙
171021	6,5W	230V ac	528lm	3 3.000K	Bl Blanco	SI
171038	6,5W	230V ac	554lm	4 4.000K	Bl Blanco	SI
412285	6,5W	230V ac	528lm	3 3.000K	Gr RAL 9006	SI
412292	6,5W	230V ac	554lm	4 4.000K	Gr RAL 9006	SI
171007	6,5W	100-240V ac	528lm	3 3.000K	Bl Blanco	NO
171014	6,5W	100-240V ac	554lm	4 4.000K	Bl Blanco	NO
412261	6,5W	100-240V ac	528lm	3 3.000K	Gr RAL 9006	NO
412278	6,5W	100-240V ac	554lm	4 4.000K	Gr RAL 9006	NO



## Fotometría/Photometry/Photométrie/Fotometria



## Bajo pedido/On request/Sur commande/A pedido



DALI



Kit de emergencia  
Emergency kit  
Kit d'urgence  
Kit de emergência

