




PRILUX

C/ Río Jarama nº 149
45007, Toledo.
Tel.: 925 23 38 12
Fax: 925 23 38 80


www.grupoprilux.com



Icon 7W BASIC




| H (m) | D (m) | E _{max} (lx) |
|-------|-------|-----------------------|
| 1 | 2.41 | 227 |
| 2 | 4.82 | 57 |
| 3 | 7.23 | 25 |
| 4 | 9.64 | 14 |



icon basic 7W

| CÓDIGO | CEE | POTENCIA | FLUJO | CCT | CASQUILLO | DIMENSIONES | REG. |
|--------|-----|----------|-------|--------|-----------|-------------|------|
| 378727 | A+ | 7W | 578lm | 3.000K | GU10 | Ø50 x 58mm | NO |
| 386326 | A+ | 7W | 605lm | 4.000K | GU10 | Ø50 x 58mm | NO |
| 378734 | A+ | 7W | 622lm | 5.000K | GU10 | Ø50 x 58mm | NO |
| 545457 | A+ | 7W | 578lm | 3.000K | GU10 | Ø50 x 58mm | SI |
| 545464 | A+ | 7W | 605lm | 4.000K | GU10 | Ø50 x 58mm | SI |
| 545471 | A+ | 7W | 622lm | 5.000K | GU10 | Ø50 x 58mm | SI |



TENSIÓN: 230V
FRECUENCIA: 50-60Hz
INTENSIDAD: 6mA
Cosφ: >0.55
T_a: -10 ~ +40° C
ÁNGULO: 100°
IRC: >80
VIDA MEDIA: 25.000h

VOLTAGE: 230V
FREQUENCY: 50-60Hz
CURRENT: 6mA
Cosφ: >0.55
T_a: -10 ~ +40° C
ANGLE: 100°
Ra: >80
LIFETIME: 25.000h

TENSION D'ALIMENTATION: 230V
FRÉQUENCE: 50-60Hz
INTENSITÉ: 6mA
Cosφ: >0.55
T_a: -10 ~ +40° C
ANGLE D'OUVERTURE: 100°
Ra: >80
HEURES DE VIE: 25.000h

TENSAO: 230V
FRECUENCIA: 50-60Hz
INTENSIDADE: 6mA
Cosφ: >0.55
T_a: -10 ~ +40° C
ÂNGULO DE ABERTURA: 100°
Ra: >80
VIDA: 25.000h